



New Compact design Compact but more Powerful CK2810 comes with new streamlined hood design, which improves visibility and service ability of the operator. A vertical opening hood allows for easy access to the air filter, fluid service, use box and electrical components for inspection.



**Powerful Environmentally Friendly Engine** The Powerful Environmentally Friendly 28hp 'Green' Engine will offer operator quietest, smoothest but most powerful working condition.



Foldable ROPS The standard foldable ROPS makes it quick and easy to maneuver in low clearance areas.



Hydraulic 4WD Front wheel driving is easily engaged by hydraulic clutch.



• Power Steering wheel With hydraulic power steering, experience smooth responsive steering that requires minimal operator effort regardless of the task at hand.



## **@** Illuminated Dashboard

The dashboard illuminates when the engine starts. The digital gauge package includes tachometer, fuel and temperature gauges along with low fuel and high temperature warning lamp.

## Specifications

MODEL			CK2810
ENGINE			
Model			3A139LWB
Туре			3Cyl, in-line Vertical, Water-cooled
Engine gross		HP	28
Displacement		сс	1,393
Rated revolution		rpm	2,600
Fuel tank capacity		Q	25
<b>DRIVE TRA</b>	IN		
Clutch			Dry single
Transmission			Manual
Transmission Speeds			6F 2R
Differential lock			Rear
Brake			Wet disc type
			Transmission
Rear PTO		rpm	540/750
Mid PTO		rpm	2,000 (Opt.)
HYDRAULIC	CSYSTEM		
Pump capacity		lpm	42.9
3-point hitch			Category
Maximum lifting capacity		kg	739
Hydraulic lift control system			Position control
Steering			Power Steering
TIRE SIZE			
AG Tire	Front		7-12
	Rear		11.2-16
TRAVELING SPEEDS			
Forward		km/h	0-17.15
Reverse		km/h	0-12.01
DIMENSION			
Overall length(including 3-pt hitch)		mm	2,790
Overall width(minimum tead)		mm	1,250
Overall height(from top of ROPS)		mm	2,108
Wheelbase		mm	1,520
Min. ground clearance		mm	330
Tread	Front	mm	989
	Rear	mm	950
Weight with ROPS		kg	1,025

\*NOTE : Specifications and design are subject to change without notice.

Standard Equipment

- Double acting valve(1ea)
- Hydraulic Power Steering
- Folderble ROPS
- Differential lock(rear)



- Front weights
- Working lamp
- 7-Pin Connector
- Mid PTO
- Rear Hydraulic valve

## Attachments

- Premium Front Loader
- Front Loader
- Mid Mount Mower
- Front PTO
- Front Linkage
- Rotary Tiler



Hong Kong | Singapore | Malaysia | Australia Email: info@centaur-asiapacific.com Website: www.centaur-asiapacific.com

