

CK3510 | CK4010

KIOTI Economical Tractor



Equipped with new Stage 4/Tier 4 engines, new CK tractor provides better engine responsiveness while maintaining the best levels of fuel consumption. The extra power is thanks to the engine power management feature which automatically boosts power to increase output for a range of work taking account of PTO operation, travel speed and load.



New CK tractors have been designed to provide high levels of performance and reliability to smaller farming and orchard business

Instrument panel provides a complete and clear display of all the information the driver needs to operate the tractor safely and efficiently.

Easy to move forward and reverse with quick step pedal



CK3510/4010

Specifications

Model		CK3510	CK4010
Manufacturer		Daedong	
Model		3B183LWM-E1	3B183LWM-E
Engine Gross Power	HP(kw)	35(26.1)	38(28.3)
Rated revolution	rpm	2600	
Engine Net Power	HP(kw)	33(24.7)	36(26.8)
No.of cylinders		3	
Total displace	cc	1826	
Bore&stroke	mm	87x102.4	
Cooling system		Water Cooled	
Lubricating system		Trochoid Pump	
Fuel Tank CAPACITY	ℓ	34	
Maximum PTO Power	HP	30.8/33.5	
PTO Efficiency	%	85%	
PTO Fuel Consumption	ℓ /h(gph)	9.08	8.38
Rear PTO		Live	
	rpm	540/750	
Mid PTO	rpm	Option(2,000)	
3-Point Lift Control Type		Positon	
HYDRAULIC			
Pump Capacity		44.1	
3-point hitch type		Category I	
Lift capacity at lift point	kg.f(lbs.)	1030	
Lift capacity at 24 in.behind lift point	kg.f(lbs.)	740	
Transmission		Manual	
DRIVE TRAIN			
No. of speeds		9 x 3	
shuttle Type		NA	
Steering		Hydrostatic Power Steering	
Brake type		Wet disc type	
Main Clutch type		Dry dual	
Differential lock		Rear Standard	
Front wheel drive system		Manual	
Forward TRAVELING SPEEDS	km/h	1.52~23.56	
Reverse	km/h	1.90~15.39	
OTHER TEATURES			
Tilt steering		N/A	
One-Touch Hood type		O	
DIMENSIONS			
Overall length (without 3-pt hitch)	mm(in.)	2701	
Overall length (includes 3-pt hitch)	mm(in.)	3010	
Overall length (with 3 point&front weight)	mm(in.)	3200	
Overall width (minimum tread)	mm(in.)	1400	
Tread width Front 4wd	mm(in.)	1132	
Tread width Rear	mm(in.)	1302	
Overall height (with ROPS)	mm(in.)	2430	
Overall height (Top of Cabin)	mm(in.)	-	
Wheel base	mm(in.)	1670	
Ground (Crop) clearance	mm(in.)	340	
Turning radius (w/brake)	mm(in.)	2450	
Weight with ROPS	kg.f(lbs.)	1300	
Weight with CABIN	kg.f(lbs.)	-	
TIRE SIZE			
Front		7-16	
Rear		11.2-24	
Turf Tire		28 X 8.5-15	41 X 14-20

Standard Equipment

- 4WD
- HST Easy Speed (40HP)
- 7 Pin Socket
- Towing Hook
- Single Lever Joystick (40HP)
- Fuel Tank cap
- Quick Type Lower Linkge (40HP)

Optional Equipment

- Mild PTO
- Front weight
- Rear weight
- Joystick valve
- Rear view mirror
- Rear Work Light
- Front Grille Guard
- Tool box
- Drawbar
- Sun Canopy

Attachments

- Premium Front Loader
- Front Loader
- Mid Mount Mower
- Front PTO
- Front Linkage
- Rotary Tiler

*NOTE : Specifications and design are subject to change without notice.