

The Rink DS1200 disc top dresser has an internal conveyor belt which moves wet or dry material to the rear of the hopper where it is dropped onto the discs for spreading up to 12m (472"). The automatic rear gate opens & closes to prevent material being dropped when in transport ensuring no mess



## Specifications

| Specifications                          |                                  |
|---|----------------------------------|
| SKU                                     | 133.120.001                      |
| Operation                               | Towed version                    |
| Spreading width (mm)                    | up to 12000                      |
| Spreading width (inch)                  | up to 472                        |
| Hopper capacity (m3)                    | 1.2                              |
| Hopper capacity (FT3)                   | 42.4                             |
| Max. Working speed (km h)               | 25                               |
| Max. Working speed (mph)                | 16                               |
| Min. Tractor HP required                | 27                               |
| Min. Oil supply of tractor (I min)      | 25                               |
| Min. Oil supply of tractor (US Gal min) | 6.6                              |
| Min. Pressure (bar)                     | 140                              |
| Min. Pressure (psi)                     | 2031                             |
| Required connections                    | 1x Double-acting hydraulic valve |
| Empty Weight (kg)                       | 490                              |
| Empty Weight (lbs)                      | 1080                             |
| Spreading width up to (mm)              | 12000                            |
| Spreading width up to (inch)            | 472                              |
|   |                                  |

**Distributed by:** 



www.centaur-asiapacific.com info@centaur-asiapacific.com

\*Hong Kong, Macau, Malaysia (Johor).