

The Verti-Cut 1300 utilises specially designed Verti-Cut blades to cut lateral grasses & promote the growth of healthy turf by removing dead plant material thus allowing better water penetration & more area for roots to grow. The Verti-Cut is easily adjustable and robust making it a favoured tool.



Specifications	
SKU	144.130.000
Operation	PTO drive
Working width (m)	1.3
Working width (inch)	51.2
Max. Working speed (km h)	Depends on conditions
Weight (kg)	155
Weight (lbs)	342
Distance between knifes (mm)	30
Distance between knifes (inch)	1.18
Min. Tractor HP required	18
Min. Lifting capacity 610 mm behind the lifting eyes (kg)	185
Min. Lifting capacity 24 inch behind the lifting eyes (lbs)	408
Max. capacity ( m² hr)	6500
Max. capacity (ft² hr)	21325
Three-point hitch	Cat
Rpm Max.	540
Gearbox oil	SAE 90
Lubricant	EP2
Dimensions (width mm)	1616
Dimensions (height mm)	801
Dimensions (length mm)	692
Dimensions (width inch)	63.6
Dimensions (height inch)	31.5
Dimensions (length inch)	27.2

## **Distributed by:**



www.centaur-asiapacific.com info@centaur-asiapacific.com

\*Hong Kong, Macau, Malaysia (Johor).