# SLLINER

## HIGH-QUALITY USER-FRIENDLY SPRAYING MACHINE

The SL Liner is a user-friendly and highly efficient marking machine that is suitable for spraying concentrates (SL Mix) and ready to use products (SL Ready, SL Direct) The SL Liner is made from high-quality materials to guarantee durability and <u>performance year after year</u>.

select

A heavy-duty frame ensures stability for optimal straight tracking ability

- High operating pressure for optimal results and low consumption
- Heavy duty battery for long operating times
- White powder-coat protects against rust and masks overspray
- > Adjustable line width
- Spray from both sides or in front
- > Fast marking

### PREFERENCES

Every operator has his or her own preferences. SL Liner can accommodate to all. SL Liner is suited for spraying straight in front as well as off to the side of the machine. The spray-parts are easily removable to be mounted on the side of the machine.

### **GENERAL USAGE**

SL Liner is suited to spray all available paints in the Selectline assortment. It is important to match the spray nozzle to the type of paint used. Amount of product used and whiteness of the line depends on the type of nozzle, pump pressure and walking speed.

### **Distributed by:**



www.centaur-asiapacific.com info@centaur-asiapacific.com

\*Hong Kong, Macau, Singapore, Malaysia & Vietnam.

### LINE MARKING MACHINES

# Selectliner

## Technical data sheet



## Distributed by:



www.centaur-asiapacific.com info@centaur-asiapacific.com

\*Hong Kong, Macau, Singapore, Malaysia & Vietnam.

## selectine

## Frame

Outer d

Outer d

W

Ba

P

Batte

**Battery life** 

Charg

Wa

Tyr

Marki

\* The outer dimensions of the Selectline possibility to install the front part on the \*\* Depending on the walking speed.
\*\*\* Depending on the usage frequency.



e material	Iron
dimensions	Carton: 85 x 65 x 50 cm
dimensions	Mounted Selectliner: ± 125 x 60 x 95 cm *
/eight	36.8 kgs
attery	Landport EV12012
Pump	Shurflo 8000-543-220
ery hours	20 hours (average 4 – 5 football fields)**
fe expectancy	± 2 years ***
ging time	10 to 12 hours (0% → 100%)
attage	12AH (20hr)
re type	Pneumatic rubber & iron rim
ing width	Adjustable discs with a width of 8, 10 and 12 cm

\* The outer dimensions of the Selectliner are various because of the adjustable handlebar height and the possibility to install the front part on the side of the Selectliner.

